

## 523

- Spine in acciaio legato
- Durezza 62-65HRC
- Precisione  $\pm 1\mu\text{m}$
- Passo 0,01 e 0,1mm

## SET SPINE CALIBRATE



523-650-51

Codice	Diametro	Passo	Numero pz
523-020-31	0.20-0.50	0.01mm	31
523-050-51	0.50-1.00	0.01mm	51
523-100-51	1.00-1.50	0.01mm	51
523-150-51	1.50-2.00	0.01mm	51
523-200-51	2.00-2.50	0.01mm	51
523-250-51	2.50-3.00	0.01mm	51
523-300-51	3.00-3.50	0.01mm	51
523-350-51	3.50-4.00	0.01mm	51
523-400-51	4.00-4.50	0.01mm	51
523-450-51	4.50-5.00	0.01mm	51
523-500-01	5.00-5.50	0.01mm	51

Codice	Diametro	Passo	Numero pz
523-550-51	5.50-6.00	0.01mm	51
523-600-51	6.00-6.50	0.01mm	51
523-650-51	6.50-7.00	0.01mm	51
523-700-51	7.00-7.50	0.01mm	51
523-750-51	7.50-8.00	0.01mm	51
523-800-51	8.00-8.50	0.01mm	51
523-850-51	8.50-9.00	0.01mm	51
523-900-51	9.00-9.50	0.01mm	51
523-950-51	9.50-10.00	0.01mm	51
523-500-41	1.0-5.0	0.1mm	41
523-500-51	5.0-10.0	0.1mm	51

## 524

- Contenitori per spine calibrate

## VALIGETTE PER SPINE CALIBRATE



524-001-01

Codice	Campo spine	Numero max.
524-001-01	0.10-10mm	51
524-001-02	10-17.5mm	72
524-001-03	17.5-25mm	50
524-001-04	25-34mm	32